## **Corporate Energy Management**

## SOLIS® CLEAR WINDOW FILM

HEAT REJECTION / REDUCES FADING / SAFETY PROTECTION

SOLIS  $70^{\text{TM}}$  is a virtually clear window film that rejects heat and reduces fading without changing the appearance of the window. SOLIS Secure has all the heat rejection and UV control properties of SOLIS  $70^{\text{TM}}$ , but combines them with an enhanced level of safety protection.\*

Performance Data – SOLIS 70		
Visible Light Transmittance 70%		
Ultraviolet (UV) Rejection > 98%		
Visible Light Reflectance 8%		
Total Solar Energy Rejected 55%		
Infrared Rejection 87%		
Performance data based on film applied to 1/8" clear monolithic glass.		

\* SOLIS Secure™ combines a heavier gauge film construction (i.e. 8.0 -mil vs. 1.5-mil) with an advanced super aggressive adhesive system. The thicker film and stronger adhesive system combine to create an almost invisible bond with the glass, minimizing the chances of glass that has been broken or shattered from being propelled at high speeds into interior areas or falling to sidewalks below the window. This also makes forced entry with a single blow virtually impossible, thwarting would-be intruders and giving police and other protection devices more time to respond.

SOLIS $^{\circ}$  Clear Window Film is available in both standard (1.5 mil thickness) or Secure (8.0 mil thickness) for extra security.

SOLIS® CLEAR WINDOW FILM COMES WITH A FULL 10 YEAR WARRANTY AGAINST PEELING, CRACKING, AND DISCOLORATION.

Solis part Number	D e s c rip tio n	NSN
Solis 3	3 ft x 100 ft	
Solis 4	4 ft x 100 ft	
Solis 5	5 ft x 1 0 0 ft	
Solis 6	6 ft x 100ft	
Solis Secure 3	3 ft x 100 ft	
Solis Secure 4	4 ft x 100 ft	
Solis Secure 5	5 ft x 100 ft	
Solis Kit	Installation kit and video (required for all the above)	

While Solis film can be installed by the end user, Corporate Energy offers a full installation service. For additional information contact the DSCP Lighting Team -1-800-DLA-BULB